



US 20190099560A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2019/0099560 A1**
(43) **Pub. Date:** **Apr. 4, 2019**(54) **ADHESIVE AND PERIPHERAL SYSTEMS
AND METHODS FOR MEDICAL DEVICES**(71) Applicant: **DEKA Products Limited Partnership,**
Manchester, NH (US)(72) Inventor: **Larry B. Gray,** Merrimack, NH (US)(21) Appl. No.: **16/192,213**(22) Filed: **Nov. 15, 2018****Related U.S. Application Data**

(63) Continuation of application No. 16/126,639, filed on Sep. 10, 2018, which is a continuation of application No. 12/617,903, filed on Nov. 13, 2009, now Pat. No. 10,071,210, which is a continuation of application No. 11/704,897, filed on Feb. 9, 2007, now Pat. No. 8,113,244.

(60) Provisional application No. 60/793,188, filed on Apr. 19, 2006, provisional application No. 60/789,243, filed on Apr. 5, 2006, provisional application No. 60/772,313, filed on Feb. 9, 2006.

Publication Classification(51) **Int. Cl.****A61M 5/50** (2006.01)**A61M 5/162** (2006.01)

(Continued)

(52) **U.S. Cl.**CPC **A61M 5/5086** (2013.01); **A61M 5/162** (2013.01); **A61M 5/142** (2013.01); **G01F 22/00** (2013.01); **A61M 5/16813** (2013.01); **A61M 5/14212** (2013.01); **A61B 5/0024** (2013.01); **A61B 5/6833** (2013.01); **A61M 5/16831** (2013.01); **A61J 1/20** (2013.01); **A61B 5/1427** (2013.01); **A61M 5/14216** (2013.01); **A61M 5/16804** (2013.01); **A61M 5/365** (2013.01); **A61M 5/1723** (2013.01); **A61M 5/158** (2013.01); **A61M 5/14244** (2013.01); **A61M 5/1452** (2013.01); **A61M 5/168** (2013.01); **A61M 5/172** (2013.01); **H04B 7/2609** (2013.01); **G08C 17/02** (2013.01); **A61M 5/16886** (2013.01); **A61M****5/16809** (2013.01); **A61M 5/14586** (2013.01); **A61M 5/14248** (2013.01); **A61M 5/14224** (2013.01); **G05D 7/0676** (2013.01); **G05D 7/0647** (2013.01); **G05B 23/02** (2013.01); **A61M 5/1413** (2013.01); **A61M 2005/1585** (2013.01); **A61M 2005/1586** (2013.01); **A61M 2205/3337** (2013.01); **A61M 2230/201** (2013.01); **A61M 2205/3303** (2013.01); **A61M 2205/3379** (2013.01); **A61M 2205/50** (2013.01); **A61M 2005/14208** (2013.01); **A61M 2205/3592** (2013.01); **A61M 2205/3523** (2013.01); **A61M 2205/3569** (2013.01); **A61M 2005/16863** (2013.01); **A61M 2205/04** (2013.01); **A61M 2205/502** (2013.01); **A61M 2205/52** (2013.01); **A61B 2560/0412** (2013.01); **Y10T 29/49826** (2015.01); **Y10T 29/494** (2015.01); **Y10T 29/49236** (2015.01); **Y10T 29/49412** (2015.01); **A61M 2005/1583** (2013.01); **A61M 2005/14252** (2013.01); **A61M 2205/8206** (2013.01); **A61M 2005/1402** (2013.01); **A61M 2205/16** (2013.01); **A61M 2205/581** (2013.01); **A61M 2205/582** (2013.01); **A61M 2205/583** (2013.01); **A61M 2005/14506** (2013.01); **A61M 2205/3368** (2013.01); **A61M 2207/00** (2013.01); **A61M 2205/18** (2013.01); **A61M 2205/0294** (2013.01); **A61M 2205/0266** (2013.01); **A61M 2005/14268** (2013.01); **A61M 2209/045** (2013.01); **A61M 2206/22** (2013.01); **A61M 2205/8237** (2013.01); **A61M 2205/3576** (2013.01); **A61M 2205/3546** (2013.01); **A61M 2205/3375** (2013.01); **A61M 2205/3331** (2013.01)

(57)

ABSTRACT

A system is disclosed. The system includes a reservoir for containing a fluidic medium, the reservoir including a front surface, a resilient cylindrical flexure portion connected to the front surface, the resilient cylindrical flexure portion comprising an accordion-like structure that is able to expand and contract to change an interior volume within the resilient cylindrical flexure portion, a central passageway within the resilient cylindrical flexure, and a collection chamber connected to the central passageway. Also, a system including a reservoir, a plunger head located within the reservoir, a plunger arm connected to the plunger head, a driving shaft connected to the plunger arm, and a motor connected to the driving shaft, the motor controllable to move the drive shaft in a first motion and a second motion so as to move the advance plunger head and retract the plunger head within the reservoir.

